avid specification

Panel End Tables & workstations

Tops 25mm thick edged 2mm matching edging, supplied as standard with a left and right hand black plastic cable port. Panel ends 25mm thick edged 2mm matching edging with levelling adjusters, 18mm thick 3/4 height modesty panels with the option of a full height modesty. Knock down construction.

Pedestals - Free Standing & Mobile

Free standing and mobile desk high pedestals have 25mm thick top edged 2mm matching edging. Desk under pedestals have 18mm thick tops edged 2mm matching edging. Drawers white with a dowel construction mounted on roller runners. All drawers to lock. Top drawer in all pedestals fitted with a pen tray. Filing drawer mounted on full extension ball bearing runners, with a deep box drawer with rails for Foolscap filing. NB the veneer grain direction on the top of 600d desk high pedestals is back to front and on 800d desk high pedestals is side to side

Filing Cabinets

2, 3 and 4 drawers. Tops 25mm thick edged 2mm matching edgings. Drawers white with a dowel construction double extension roller runners and fitted, with a deep box drawer with rails for Foolscap filing side to side. All drawers to lock, with integral anti tilt mechanism. NB the veneer grain direction on the filing cabinet tops is back to front.

Side Filer

Tops 25mm thick edged 2mm matching edgings. Drawers have pull out filing frames for A4/Foolscap filing mounted on heavy duty double extension runners. Both drawers to lock, with integral anti tilt mechanism. NB the veneer grain direction on the side filer top is side to side

Sliding Door Storage

Tops 25mm thick edged 2mm matching edgings, fitted adjustable shelf enclosed by locking sliding wood doors. Larger units fitted central divider with adjustable shelf each side. NB the veneer grain direction on the storage top is side to side.

Hinged Door and Desk Side Storage

Tops 25mm thick edged 2mm matching edgings, fitted adjustable shelf enclosed by locking hinged wood doors. Larger units fitted central divider with adjustable shelf each side and 2 pairs of locking hinged doors. NB the veneer grain direction on the desk side storage top is back to front.

Open Fronted Bookcase

Floor standing bookcase unit. Tops 25mm thick edged 2mm matching edgings supplied with adjustable shelves.

Sliding Glass Door Bookcase

Tops 25mm thick edged 2mm matching edgings. Fitted 2 (no) adjustable wooden shelves enclosed by non-locking clear sliding glass doors with finger notch for opening. Glass shelves and display lighting are available as an optional extra.

Hinged Door Lateral Storage

Tops 25mm thick edged 2mm matching edgings. Cabinet fitted locking hinged wood doors. End panels drilled full height at 32mm centres to accept either wood shelves or Hettich lateral filling fittings (not included).

Side Opening Tambour Fronted Lateral Storage

Tops 25mm thick edged 2mm matching edging. Fitted with locking silver plastic side opening tambour. NB Cabinet will only take 760 lateral fittings

Lateral Storage Fittings

Shelves • Wood
Pull out filing frames • Steel
Hat shelf. Hanging rail • Wood/Steel
Door Mirror • Glass

Meeting Tables

Tops 25mm thick edged 2mm matching edgings. The veneered tops have the grain direction running along the length, single piece MFC tops grain direction along the length. Multi section MFC tops grain runs across the width. Tops come with three top shapes: Rectangular, Semi-Circular Ended and Barrel. All top shapes come with three leg options: panel end base, open frame base and pedestal base. The open frame and pedestal base as standard are white.

Coffee Tables

Tops 25mm thick edged 2mm matching edgings mounted on white pedestal base. Coffee tables come with two top shapes square and circular

avid specification

Cross Banding

A complementary veneer is combined with a black inlaid line detail to create a decorative border around the door panels. The cross banding is available in various standard options.

For cross banding veneer pricing the main inner panel door veneer finish determines the price band.

The Avid Range

A range of modular stacking cabinets available in two standard widths, a standard depth with 3 height options to allow flexibility in the layout. The system is designed with the integration of AV equipment in mind and the cabinets are designed to create a void behind the cupboard runs for cabling along with the option of standard wire management cut outs.

Plinths

All base units are supplied with integrated 100mm plinth. The plinths are fitted with 4 metal levelling adjusters accessed from inside the cabinet.

Cabinets

Cabinets are specified as either base units including a plinth for floor standing or as top units for stacking on top of a base unit. The cabinets are either open fronted, fitted with locking hinged wood doors, non-locking hinged glass doors or on the 2000 series 800 unit only available with lateral filing drawers. The cabinet carcases come with both the left and right hand ends projecting 50mm past the inset back, to create a cavity for cable routing or to allow for end panel scribing for uneven or out of square walls. All adjoining end panels are drilled to allow adjacent cupboards to be bolted together.

NB All storage runs above the 1200 height should be secured back to the wall.

Cupboard Internal Fittings

All base and top units except filing drawer modules are supplied without internals. The required fittings are specified and costed as additional requirements.

Wooden Shelves

Standard 25mm thick with 0.6 edge veneer on front edge mounted on standard adjustable shelf clips. Shelf finished in a veneer to match the internal carcase finish.

Glass shelf

6mm toughened clear glass shelves mounted on standard adjustable shelf clips.

Wire Management Options

WM1 Base unit - 300mm L x 150mm H cut out in the back panel at the bottom for access to wall sockets with 80 dia cable port in the top of the back panel for cable routing. This option applies to the 2000 and 4000 series base units.

WM2 Top units - 2×80 dia cable ports fitted in the top and the bottom of the back panel for cable routing. This option applies to the 4000 series top units.

WM3 Base Unit - 300mm L \times 150mm H cut out in the back panel at the bottom for access to wall sockets with 2×80 dia cable ports in the middle and top of the back panel for cable routing. This option applies to the 6000 series base units.

WM4 Audio-visual - 4 x 80-dia cable ports in the top and bottom corners of the back panel for cable routing. This option applies to the 7000 series top unit.

WMT - Wire management trunking, a simple 3 compartment plastic trunking supplied in 1.5m lengths for managing cable routing.

Pull out Filing Frame

Standard steel pull out filing cradle mounted on full extension ball bearing runners. Pull out cradles available with integral anti-tilt system.

NB Pull out cradles should only be fitted in base units.

Hanging Rail

Chrome hanging rail supplied with 2 screw fix end caps.

Fridge

A 2 cuft fridge is supplied to fit within the cupboard. This option is only available on the 2000 series base unit. The cupboard where this option is selected is supplied as standard with an offset divider panel with the fridge fitted on the left hand side and 2 adjustable narrow shelves to the right hand side. The left-hand side back panel is cut out for fridge ventilation.

Low Voltage Lighting

Fitted with single low voltage light fitting and supplied with single transformer unit. When more than one light fitting is required the single transformer is used to power up to a maximum of 4 separate units.

NB transformer 13amp plug not supplied.

Dry Wipe Option

Both inside faces of the doors on the audio visual unit are finished in white gloss laminate.

Top Fascia Panels

The top fascia is designed either as a decorative fascia or as a scribing component where the cupboards are fully fitted to the ceiling. The height of the fascia is 100mm as standard to match the plinth height. The height can be specified for fully fitted installations.

Side Infill Panel

18mm thick panel edged 2mm thick veneer all round. The panel is supplied with fixing fillets and brackets to allow scribing to walls where the cupboard run is fully fitted. The length and width should be specified to suit the application.

Corner Infill

18mm thick panels to match adjacent cupboards. The panel is supplied with fixing screws to space adjacent cupboards that are fitted into a 90 degree corner.